

# **QPS, KW-hr, MTBF, $\Delta T$ , PUE, IOPS, DB/RH: A *Day in a Life of a Datacenter Architect***

*Kushagra Vaid*

*Principal Architect, Datacenter Infrastructure*

*Microsoft Online Services Division*

*[kvaid@microsoft.com](mailto:kvaid@microsoft.com)*

# First... lets explain the lingo in the talk title...

Metric	Definition	Usage
QPS	Queries per second	Performance of Index-serving engine
KW-hr	Kilowatt-hr: Energy consumption metric	Effectiveness of power conservation schemes
MTBF	Mean Time Between Failures	Understanding component reliability
$\Delta T$	Temperature delta between front and rear of server	Server chassis design and airflow CFD analysis
PUE	Power Usage Effectiveness	Measure of datacenter power efficiency
IOPS	Disk Input/Output Operations per second	Storage subsystem performance analysis
DB/RH	Dry Bulb: Air temperature Wet Bulb: Temperature indicating amount of moisture in the air	Determining server operating range and acceptable environmental specs

# Microsoft Datacenters: Providing services 24x7



More than 1 billion authentications per day



More than 2 billion queries per month



Processes 2–4 billion e-mails per day



320 million active accounts




550 million unique visitors monthly



400 million active accounts

# Microsoft Datacenters – Global scaling!

Multiple global CDN locations in the Americas, Europe and APAC.



Quincy, Washington: approx 500K sq ft, 27MW, uses entirely hydro-electric power

San Antonio, Texas: approx 477K sq ft, 27MW, uses recycled water for cooling

Chicago, Illinois: 707,000 square feet with critical power of 60 MW, uses water side economization, containers

Dublin, Ireland: approx 570K sq ft, up to 27MW, uses outside air for cooling.

"Datacenters have become as vital to the functioning of society as power stations." – *The Economist*



A large mega-datacenter is  
**11 times**  
the size of a football field



# Design factors for Datacenter Infrastructure

## Datacenter and Server architecture

- Power distribution efficiency
- Cost efficiency
- Thermal design analysis

## Platform architecture

- Application performance analysis
- New platform architecture exploration

## Reliability analysis

- Environmental operating ranges and impact on MTBF

## Bringing it all together – Holistic Systems Design

# Design factors for Datacenter Infrastructure

## Datacenter architecture

- **Power distribution efficiency**
- Cost efficiency
- Thermal design analysis

## Platform architecture

- Application performance analysis
- New platform architecture exploration

## Reliability analysis


- Environmental operating ranges and impact on MTBF

## Bringing it all together – Holistic Systems Design

# Cost and efficiency facts

For a typical large mega-datacenter...

Building costs are between \$10M to \$15M per MegaWatt





More about PUE: <http://thegreengrid.org/en/Global/Content/white-papers/The-Green-Grid-Data-Center-Power-Efficiency-Metrics-PUE-and-DCiE>

Typical industry PUE ranges from 1.5-2.0

Energy Consumption: US power rate 10.27 cents per Kilowatt hour) according to DOE/eia ([http://www.eia.doe.gov/cneaf/electricity/epm/table5\\_3.html](http://www.eia.doe.gov/cneaf/electricity/epm/table5_3.html))


# Facility level distribution options

Consider the following common topologies ...



# Analyzing Facility level distribution efficiency

Which topology is the most efficient (lowest PUE)?




Double Conversion 480Vac - 208Vac	Line Interactive 480Vac - 208Vac	Double Conversion 600Vac - 208Vac	Line Interactive 600Vac - 208Vac
Double Conversion 480Vac - 277Vac	Line Interactive 480Vac - 277Vac	Double Conversion 480Vac - 240Vac	Line Interactive 480Vac - 240Vac
480Vac - 48Vdc	480Vac - 575Vdc - 48Vdc	480Vac - 380Vdc	

Source: Green Grid ([http://www.thegreengrid.org/~media/WhitePapers/White\\_Paper\\_16\\_-\\_Quantitative\\_Efficiency\\_Analysis\\_30DEC08.ashx](http://www.thegreengrid.org/~media/WhitePapers/White_Paper_16_-_Quantitative_Efficiency_Analysis_30DEC08.ashx))

# Challenges with datacenter power allocation


SPECpower2008 benchmark  
2 x Intel L5640/6c/2.26Ghz  
16GB DDR3  
1x160GB SSD  
Windows Server 2008 R2



[http://www.spec.org/power\\_ssj2008/results/res2010q3/power\\_ssj2008-20100714-00275.html](http://www.spec.org/power_ssj2008/results/res2010q3/power_ssj2008-20100714-00275.html)

- Problem statement: Given the above power load curve, how would you maximize server density for the datacenter power envelope
- Tradeoffs:
  - Provision based on peak load → stranded power from variable load traffic patterns
  - Provision based on average load → risk of tripping circuit breakers at higher load levels

# Challenges with datacenter power allocation



Output of datacenter power meter

- Short duration power spikes from sudden load increases occur in reality
- Server heterogeneity and app power profile changes also need to be considered
- Power Capping can be used, but requires understanding tradeoff to performance SLAs and may require sophisticated policy management
- The eventual allocation is a calculated risk to maximize server density without stranding power, taking load patterns into consideration

# Design factors for Datacenter Infrastructure

## Datacenter architecture

- Power distribution efficiency
- **Cost efficiency**
- Thermal design analysis

## Platform architecture

- Application performance analysis
- New platform architecture exploration

## Reliability analysis


- Environmental operating ranges and impact on MTBF

## Bringing it all together – Holistic Systems Design

# Datacenter TCO breakdown

## Assumptions:

10MW facility  
PUE 1.25  
\$10/W construction costs  
\$0.10c/KWhr power costs  
Server: \$2000, 200W  
3yr server amortization  
15yr datacenter amortization



Source: James Hamilton (<http://mvdirona.com/jrh/TalksAndPapers/PerspectivesDataCenterCostAndPower.xls>)

- Datacenter build costs are 17% of TCO
- Energy usage costs are 16% of TCO
- Server capex accounts for largest portion of TCO (61%)
  - Invest in mechanisms to improve work done per watt

# Microsoft's Datacenter Evolution

Datacenter Colocation  
Generation 1



2005

**Server**

Capacity  
~2 PUE

San Antonio & Quincy  
Generation 2



2006

**Rack**

Density and  
Deployment  
1.4 – 1.6 PUE

Chicago & Dublin  
Generation 3




2008

**Containers & Pods**

Scalability and  
Sustainability  
1.2-1.5 PUE

Modular Datacenter  
Generation 4



2009

2010+

**ITPAC**

Faster Time to Market  
Reduced Carbon  
1.05-1.15 PUE

DEPLOYMENT SCALE UNIT

EFFICIENT RESOURCE USAGE



# Microsoft's Chicago Data Center

\$500M+ investment

3000 construction related jobs

707,000 sq ft


60 MW Total Critical Power

1.5 million man-hours-of-labor

3400 tons of steel

190 miles of conduit

2400 tons of copper



7.5 miles of chilled water piping

26,000 cubic yards of concrete



# Design factors for Datacenter Infrastructure

## Datacenter architecture

- Cost efficiency
- Power distribution efficiency
- **Thermal design analysis (CFD modeling)**

## Platform architecture

- Application performance analysis
- New platform architecture exploration

## Reliability analysis

- Environmental operating ranges and impact on MTBF

Bringing it all together – Holistic Systems Design

ITPAC design overview  
(showing thermal modeling and  
construction)

*video*



The image features the Microsoft logo in a bold, italicized, white font with a registered trademark symbol, set against a background of a bright blue sky filled with fluffy white clouds. The logo is positioned in the upper half of the frame.

**Microsoft<sup>®</sup>**

IT Pre-Assembled-Components  
(ITPAC)

# Design factors for Datacenter Infrastructure

## Datacenter architecture

- Cost efficiency
- Power distribution efficiency
- Thermal design analysis

## Platform architecture

- **Application performance analysis**
- New platform architecture exploration



## Reliability analysis

- Environmental operating ranges and impact on MTBF

Bringing it all together – Holistic Systems Design

# CPU pipeline analysis

## Bing CPI comparisons



Stall cycle breakdown


Instruction Mix

Sources of cache access

Source: Reddi et al, "Web Search using Mobile Cores: Quantifying the Price of Efficiency, ISCA 2010

- Bing is computationally intensive and exhibits good instruction level parallelism
- Most memory operations are loads (as expected) for index reads
- Pipeline stalls due to cache misses are small (~7%) relative to other stall events
- Analysis helps understand how to optimize code for maximizing **QPS (Queries per Second)**

# Workload scalability analysis





Performance scaling as a function of processor frequency and number of cores for Bing and Cosmos.

Source: Kozyrakis et al, "Server Engineering Insights for Online Services, IEEE Micro, July 2010


- How does the multicore trend affect online workloads?
- Identify workload scalability bottlenecks if any
- What is the tradeoff for different frequency offerings in commodity CPUs?

# Storage rightsizing for power provisioning efficiency

Property	Randomness			RD:WR Ratio	Read					Write				
	Total	RD	WR		4K	8K	16K	32K	64K	4K	8K	16K	32K	64K
MSG-EMAIL	93%	93%	94%	4.7	57%	5%			8%	14%				
MAPS	27%	24%	96%	19.8	14%				65%	4%				
USER CONTENT	91%	90%	98%	7.0	70%					10%				



Provisioning through Trace-Driven Approach



Sankar et al, "Storage Characterization for Unstructured Data in Online Services Applications", IISWC 2009

Sankar et al, "Addressing the Stranded Power Problem in Datacenters Using Storage Workload Characterization", WOSP-SIPEW 2010

- E.g. above shows how in-depth storage trace analysis can be used to understand I/O workload patterns and **IOPS rates**
- HDD power models can then be used to determine optimal power provisioning values – minimizing stranded power and allowing higher density

# Design factors for Datacenter Infrastructure

## Datacenter architecture

- Cost efficiency
- Power distribution efficiency
- Thermal design analysis

## Platform architecture

- Application performance analysis
- **New platform architecture exploration**


## Reliability analysis

- Environmental operating ranges and impact on MTBF


Bringing it all together – Holistic Systems Design

# Evaluating mobile CPUs (Atom) for Bing

- Concept: Scale down the Bing platform to use ultra-low power mobile CPUs
  - Advantages: Low cost and power
  - Disadvantages: Performance, Significant tuning
- Results below show how the current systems compare
  - Overall, Xeon systems are currently 2.3x better than Atom on a Perf/W/\$ basis
  - Atom system power is high, even though CPU power is low (few watts)
  - However, significant room for improvements as Atom-based servers are optimized in the future



# CPU pipeline analysis for Atom





- Atom CPU weak on Branches, FP and caches → 3x worse CPI
- Overall TCO is 2.5x worse on both Perf/\$ and Perf/Watt
- Need future Atom CPUs to either provide improved perf or much lower power
- *Source: "Web Search Using Mobile Cores", ISCA 2010*

	Xeon		Atom			
	Harpertown 4-core, 2-socket		Diamondville 2-core, 1-socket		Hypothetical 8-core, 2-socket	
	Cost (\$)	Power (W)	Cost (\$)	Power (W)	Cost (\$)	Power (W)
Processor	760	125	45	3.2	760	25.6
Motherboard	200	30	80	30	200	30
Network Interface	0	5	0	5	0	5
Memory (4GB)	150	8	150	8	150	8
Storage (HDD)	100	10	100	10	100	10
Total Server Cost	1210	178	375	56.2	1210	78.6
Efficiency × 10 <sup>-3</sup>	6.38	43.37	2.67	17.79	6.61	101.78
	QPS/\$	QPS/W	QPS/\$	QPS/W	QPS/\$	QPS/W

# Improving Perf/W for SQL workloads

- Seek architectural opportunities for *dramatic* Perf/W improvements
- E.g. shown below for SSD caching solutions implemented in HW RAID controllers and in SW buffer pool management algorithms
- Upto ~3x server consolidation possibility for database workloads



*Khessib et al, "Using Solid State Drives as a Mid-Tier Cache in Enterprise OLTP applications", TPC Technology Conference on Performance Evaluation and Benchmarking (TPC-TC), Sept 2010*

# Design factors for Datacenter Infrastructure

## Datacenter architecture

- Cost efficiency
- Power distribution efficiency
- Thermal design analysis

## Platform architecture


- Application performance analysis
- New platform architecture exploration

## **Reliability analysis**

- **Environmental operating ranges and impact on MTBF**

Bringing it all together – Holistic Systems Design

# Server operating range specification



Source: [http://media.techtarget.com/digitalguide/images/Misc/temp\\_hr.gif](http://media.techtarget.com/digitalguide/images/Misc/temp_hr.gif)

ASHRAE recommended range: 64F-81F Drybulb, max 60% RH

However, most server vendors specify 50F-95F, max 90%RH

Higher temperature operation → Lower fan speeds to cool servers → Improved PUE


However, need to take into account reliability aspects for server components

# Temperature sensitivity analysis

HDD-TEMP	B-1	B-2	B-3	B-4	B-5	B-6	B-7	B-8	B-9	B-10	B-11	B-12	B-13	B-14	B-15	B-16	B-17	B-18	B-19	B-20	B-21	B-22	B-23	B-24	B-25	B-26	B-27	B-28	B-29	B-30	B-31	B-32	B-33	B-34	
27 C																																			
28 C						6.7%																													
29 C						70.2%																													
30 C	0.3%	0.3%		37.4%	15.1%	22.9%																													
31 C	65.0%	59.4%	56.0%	56.7%	74.3%	0.1%	38.4%																												
32 C	33.3%	37.4%	40.6%	5.8%	10.5%		56.5%																												
33 C	1.4%	2.9%	3.3%				5.1%																												
34 C																																			
35 C																																			
36 C								7.0%								10.8%																			
37 C								71.4%					3.3%	68.2%																					
38 C								21.0%		1.1%	0.4%		67.5%	20.5%																					
39 C								0.5%	0.4%	47.9%	33.0%		26.6%	0.5%																				0.4%	
40 C								44.7%	44.4%	53.4%	16.5%	2.5%									0.1%							2.6%						22.6%	
41 C								42.4%	6.4%	12.6%	55.3%		4.1%								20.6%						1.2%	36.1%						45.9%	
42 C								12.4%	0.1%	0.6%	26.5%		59.9%								8.3%	59.0%	27.4%				36.5%	46.1%						28.5%	
43 C								0.1%			1.7%		30.1%								58.4%	20.1%	53.3%				50.6%	15.0%						2.5%	
44 C													5.9%	3.5%	1.0%						26.5%	0.2%	16.8%	0.5%			0.1%	10.4%	0.1%	9.0%		0.7%	1.4%		
45 C																47.0%	24.0%	3.2%	5.9%		6.8%		2.5%	25.6%		0.2%	11.5%	1.3%		44.1%	14.6%	23.7%	26.9%		
46 C																33.1%	49.6%	18.6%	27.6%					43.4%	1.6%	5.9%	47.9%		31.6%	35.8%	39.2%	45.4%			
47 C																15.7%	24.1%	56.6%	51.8%					26.0%	28.2%	45.8%	34.8%		15.1%	38.4%	31.1%	24.4%			
48 C																0.6%	1.3%	18.7%	13.4%					4.5%	41.2%	1.1%	36.0%	5.5%		0.2%	10.9%	5.4%	1.9%		
49 C																		2.8%	1.2%					0.0%	25.9%	19.8%	11.7%	0.1%							
50 C																									3.0%	44.5%	0.4%								
51 C																									0.0%	26.5%									
52 C																										7.8%									
53 C																										0.2%									

- HDD case temp distribution shown for a 35-bay JBOD array (over 3 months) for fixed server inlet temperature (25C)
- **Note increase in  $\Delta T$**  for inner drive bays
- Airside economization scenarios may imply higher inlet temperatures - **What are implications to HDD MTBF?**

# Modeling HDD AFR sensitivity to temperature



- Model the HDD Failure Acceleration Factor, adjusted for production failure data (left figure)
- Create mapping based on temperature distribution data (figure below)
- Calculate overall AFR for a given input server inlet temperature

COMPUTING ACCELERATION FACTOR FOR HDD																																		
SERVER INLET	B-1	B-2	B-3	B-4	B-5	B-6	B-7	B-8	B-9	B-10	B-11	B-12	B-13	B-14	B-15	B-16	B-17	B-18	B-19	B-20	B-21	B-22	B-23	B-24	B-25	B-26	B-27	B-28	B-29	B-30	B-31	B-32	B-33	B-34
10 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
11 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
12 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
13 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
14 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
15 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
16 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
17 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
18 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
19 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
20 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
21 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
22 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
23 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
24 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
25 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
26 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
27 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
28 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
29 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
30 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
31 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
32 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
33 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
34 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
35 C	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3

# Design factors for Datacenter Infrastructure

## Datacenter architecture

- Cost efficiency
- Power distribution efficiency
- Thermal design analysis

## Platform architecture

- Application performance analysis
- New platform architecture exploration


## Reliability analysis

- Environmental operating ranges and impact on MTBF

## **Bringing it all together – Holistic Systems Design**

# Optimal systems design (Infrastructure perspective)

## Multi-dimensional optimization problem



# Research areas

- Optimal Power provisioning for high dynamic range workloads (idle at night, peak load during day)
- Power aware task scheduling on large clusters
- Energy proportionality via system architecture innovations
- Reliability model for entire datacenter, correlated for parameters such as temperature, humidity, load levels
- Failure prediction opportunities based on log analysis of continuous feeds from management consoles
  
- Several others...

# Summary

- Datacenter design and optimization for various application scenarios involves several disciplines with complex interactions
- An optimal design is usually a delicate balance between various tradeoffs – no easy answers
- Extensive data analysis is the key to making effective design choices
- Several areas for improved design and reliability via data mining and predictive analysis

Q & A